Integrated Modelling of ITER plasma scenarios in the SRO phase

F. Koechl¹, R. Futtersack², Y. Baranov², X. Bonnin¹, C. Bourdelle³, F. Casson², M. Cavinato⁴,
M. Dubrov¹, F. Eriksson², L. Figini⁵, P. Fox², L. Garzotti², Y. Gribov¹, O. Hoenen¹, E. Khayrutdinov⁶,
R. R. Khayrutdinov⁶, B. Kim⁷, S.-H. Kim¹, P. Knight², S. V. Konovalov⁶, J. Lee¹, A. Loarte¹,
V. Lukash⁶, S. Medvedev⁸, E. Militello-Asp², V. Parail², S. D. Pinches¹, R. A. Pitts¹, A. R. Polevoi¹,

A. Pshenov¹, M. Schneider¹, J. Simpson², Z. Stancar², P. Strand⁹, G. Suarez Lopez¹, D. Taylor², E. Tholerus²

¹ITER Organization, Route de Vinon-sur-Verdon, CS 90 046, 13067 St. Paul lez Durance Cedex, France ²United Kingdom Atomic Energy Authority, Culham Science Centre, Abingdon, OX14 3DB, UK ³CEA, IRFM, 13108 St. Paul-lez-Durance, France

⁴Fusion For Energy Joint Undertaking, Josep Pla 2, 08019 Barcelona, Spain

⁵Istituto di Fisica del Plasma, Consiglio Nazionale delle Ricerche, 20125 Milano, Italy

⁶National Research Center "Kurchatov Institute", Moscow, 123182 Russia

⁷Department of Nuclear Engineering, Seoul National University, Seoul, Korea

⁸Keldysh Institute of Applied Mathematics, Miusskaya 4, 125047 Moscow, Russian Federation

⁹Chalmers University of Technology, Göteborg, Sweden

The ITER Research Plan (IRP) has been re-developed with consideration of a tungsten wall and a new heating mix. The envisioned operation stages consist of an initial Start of Research Operation (SRO) phase in which 40 MW EC-heated Hydrogen L-mode scenarios up to $I_{pl} = 15$ MA and $B_0 = 5.3$ T and Deuterium H-mode scenarios up to $I_{pl} = 7.5$ MA and $B_0 = 2.65$ T are foreseen to be established. In this context, new integrated simulations are necessary to predict plasma performance and operational constraints with tungsten as the main heavy ion impurity.

For this purpose, the High Fidelity Plasma Simulator (HFPS), comprised of the DINA free boundary equilibrium evolution code the **JINTRAC** and integrated core (JETTO + SANCO + TGLF-SAT2) + edge / SOL-div (EDGE2D + EIRENE) transport solvers embedded in the IMAS workflow environment have been applied. Full scenario calculations, focusing on H-mode scenarios and H-mode accessibility, have been performed for the limiter, current ramp-up, flat-top and ramp-down phases including a scan of the impact of W sputtering at the wall as function of SOL transport conditions, and constraints on the operational space have been assessed. In particular, the core contamination efficiency of W released at the wall vs. the divertor and options for actuator adjustment in each phase of the scenario for the minimisation of core W accumulation have been evaluated. It is shown that it is possible to operate at quasistationary conditions at a high W self-sputtering induced core radiation fraction of ~70-80% in the limiter phase provided that central EC heating in excess of the central radiation losses is continuously applied. In the diverted current ramp-up phase, the W core concentration is predicted to reduce strongly when the plasma is moved away from the wall at X-point formation and while the W sputtering source at the divertor remains negligible due to modest predicted temperatures and power densities at the targets of up to a few MW/m² with moderate EC heating of $P_{EC} \leq 20 \; MW$ and a Greenwald density fraction $n_{e,lin.\text{-}avg.}/n_{GW}$ ~0.4. In the flat-top phase, divertor heat flux control by Ne seeding may be required despite efficient W screening in the pedestal in Hmode in case of operation at lower densities below $n_{e,lin-avg}/n_{GW} < 0.4$ at $P_{EC} = 40$ MW. For the ramp-down phase, strategies for an optimum H-mode termination, heating, fuelling and plasma shape evolution schedule for a well controllable plasma termination at minimum W contamination are exemplified.